

 <p>EN AW 2007 AlCu4PbMgMn</p>		
Tyč kruhová lisovaná		
Dodací rozměr:	Mechanický stav:	Teoretická hmotnost kg/m:
Ø 20	T4511	0,895
Ø 22	T4511	1,083
Ø 25	T4511	1,398
Ø 26	T4511	1,512
Ø 28	T4511	1,754
Ø 30	T4511	2,014
Ø 32	T4511	2,291
Ø 35	T4511	2,741
Ø 36	T4511	2,899
Ø 38	T4511	3,231
Ø 40	T4511	3,580
Ø 42	T4511	3,947
Ø 45	T4511	4,530
Ø 50	T4511	5,593
Ø 52	T4511	6,050
Ø 55	T4511	6,768
Ø 56	T4511	7,016
Ø 60	T4511	8,054
Ø 63	T4511	8,880
Ø 65	T4511	9,452
Ø 70	T4511	10,963
Ø 75	T4511	12,585
Ø 80	T4511	14,318
Ø 85	T4511	16,164
Ø 90	T4511	18,122
Ø 95	T4511	20,191
Ø 100	T4511	22,373
Ø 105	T4511	24,666
Ø 110	T4511	27,071
Ø 120	T4511	32,216
Ø 125	T4511	34,957
Ø 130	T4511	37,810
Ø 135	T4511	40,774
Ø 140	T4511	43,850
Ø 150	T4511	50,338
Ø 155	T4511	53,750
Ø 160	T4	57,274
Ø 165	T4	60,909
Ø 170	T4	64,657

Ø 175	T4	68,516
Ø 180	T4	72,487
Ø 185	T4	76,570
Ø 190	T4	80,765
Ø 195	T4	85,071
Ø 200	T4	89,490
Ø 210	T4	98,663
Ø 220	T4	108,283
Ø 230	T4	118,351
Ø 240	T4	128,866