



EN AW 2024
AlCu4Mg1

Tyč kruhová lisovaná

Dodací rozměr:	Mechanický stav:	Teoretická hmotnost kg/m:
Ø 12	T3511	0,317
Ø 14	T3511	0,431
Ø 15	T3511	0,495
Ø 16	T3511	0,563
Ø 18	T3511	0,712
Ø 20	T3511	0,879
Ø 22	T3511	1,064
Ø 25	T3511	1,374
Ø 28	T3511	1,723
Ø 30	T3511	1,978
Ø 32	T3511	2,251
Ø 35	T3511	2,693
Ø 36	T3511	2,849
Ø 40	T3511	3,517
Ø 45	T3511	4,451
Ø 50	T3511	5,495
Ø 55	T3511	6,847
Ø 60	T3511	7,913
Ø 65	T3511	9,287
Ø 70	T3511	10,770
Ø 75	T3511	12,364
Ø 80	T3511	14,067
Ø 85	T3511	15,881
Ø 90	T3511	17,804
Ø 100	T3511	21,980
Ø 110	T3511	26,596
Ø 120	T3511	31,651
Ø 130	T3511	37,146
Ø 140	T3511	43,081
Ø 150	T3511	49,455
Ø 160	T3511	56,269
Ø 170	T3	63,522
Ø 180	T3	71,215
Ø 200	T3	87,920
Ø 220	T3	106,383
Ø 240	T3	126,605
Ø 250	T3	137,375
Ø 260	T3	148,585
Ø 280	T3	172,323
Ø 300	T3	197,820