

 <p>EN AW 6082 AlSi1MgMn</p>		
Tyč kruhová lisovaná		
Dodací rozměr:	Mechanický stav:	Teoretická hmotnost kg/m:
Ø 20	T6511	0,848
Ø 22	T6511	1,026
Ø 25	T6511	1,325
Ø 26	T6511	1,433
Ø 28	T6511	1,662
Ø 30	T6511	1,908
Ø 32	T6511	2,170
Ø 35	T6511	2,596
Ø 36	T6511	2,747
Ø 38	T6511	3,061
Ø 40	T6511	3,391
Ø 42	T6511	3,739
Ø 45	T6511	4,292
Ø 48	T6511	4,883
Ø 50	T6511	5,299
Ø 52	T6511	5,731
Ø 55	T6511	6,411
Ø 56	T6511	6,647
Ø 58	T6511	7,130
Ø 60	T6511	7,630
Ø 63	T6511	8,412
Ø 65	T6511	8,955
Ø 70	T6511	10,386
Ø 75	T6511	11,922
Ø 80	T6511	13,565
Ø 85	T6511	15,313
Ø 90	T6511	17,168
Ø 95	T6511	19,128
Ø 100	T6511	21,195
Ø 105	T6511	23,367
Ø 110	T6511	25,646
Ø 115	T6511	28,030
Ø 120	T6511	30,521
Ø 125	T6511	33,117
Ø 130	T6511	35,820
Ø 135	T6511	38,628
Ø 140	T6511	41,542
Ø 145	T6511	44,562
Ø 150	T6511	47,689

Ø 155	T6511	50,921
Ø 160	T6511	54,259
Ø 165	T6511	57,703
Ø 170	T6511	61,254
Ø 180	T6	68,672
Ø 185	T6	72,540
Ø 190	T6	76,514
Ø 200	T6	84,780
Ø 210	T6	93,470
Ø 220	T6	102,584
Ø 230	T6	112,122
Ø 240	T6	122,083
Ø 250	T6	132,469
Ø 260	T6	143,278
Ø 270	T6	154,512
Ø 280	T6	166,169
Ø 290	T6	178,250
Ø 300	T6	190,755