

 <p><b>EN AW 7075</b> <b>AlZn5,5MgCu</b></p>		
Tyč kruhová lisovaná		
Dodací rozměr:	Mechanický stav:	Teoretická hmotnost kg/m:
Ø 12	T6511	0,322
Ø 14	T6511	0,439
Ø 15	T6511	0,503
Ø 16	T6511	0,573
Ø 18	T6511	0,725
Ø 20	T6511	0,895
Ø 22	T6511	1,083
Ø 25	T6511	1,398
Ø 28	T6511	1,754
Ø 30	T6511	2,014
Ø 32	T6511	2,291
Ø 35	T6511	2,741
Ø 36	T6511	2,899
Ø 40	T6511	3,580
Ø 45	T6511	4,530
Ø 50	T6511	5,593
Ø 52	T6511	6,050
Ø 55	T6511	6,786
Ø 56	T6511	7,016
Ø 60	T6511	8,054
Ø 65	T6511	9,452
Ø 70	T6511	10,963
Ø 75	T6511	12,585
Ø 80	T6511	14,318
Ø 85	T6511	16,164
Ø 90	T6511	18,122
Ø 95	T6511	20,191
Ø 100	T6511	22,373
Ø 105	T6511	24,666
Ø 110	T6511	27,071
Ø 115	T6511	29,588
Ø 120	T6511	32,216
Ø 130	T6511	37,810
Ø 140	T6511	43,850
Ø 150	T6	50,338
Ø 160	T6	57,274
Ø 170	T6	64,657
Ø 180	T6	72,487
Ø 190	T6	80,765

Ø 200	T6	89,490
Ø 210	T6	98,663
Ø 220	T6	108,283
Ø 230	T6	118,351
Ø 240	T6	128,866
Ø 250	T6	139,828
Ø 260	T6	151,238
Ø 280	T6	175,400
Ø 300	T6	201,353
Ø 320	T6	229,094
Ø 350	T6	274,063
Ø 400	T6	357,960
Ø 450	T6	453,043
Ø 500	T6	559,313